

## Schultze Breuer Aggregate Tester

## **Introduction:**

This unit is used to measure system integrity and compatibility of microsurfacings. This is critical in design of mixes and is a part of the standard specification of most authorities including the International Slurry Surfacing Association. It is essential for ISSA TB 144.

## **Specification:**

- Type : CM-100
- Air pressure: 0- 6bar
- Sizes: 30\* 43 \* 43 cm
- Weight: 25 kg



## **Includes:**

- 4 pairs (8) tumbling shuttle cylinders
- I/6 HP 115/230 V 50/60 Hz
- 367 lbs. approximate shipping weight
- also applies to 230 V 50/60 Hz
- Items below usually required with Schulze-Breuer purchase:
- Schulze-Breuer 40 gram pill molds
- Schulze-Breuer constant force pneumatic pill press - up to 1 ton capacity
- 96 lbs. approximate shipping weight
- 10" x 25" x 16"
- 40 psi = 2,000 lbs. force
- Ruck adhesion and integrity procedure baskets (set o



Schultze Breuer Aggregate Tester

Jiaxing Mide Machinery Co., LtD. Tel: 0573-83121173 Fax: 0573-83121153 Schultze Breuer Aggregate Tester website: www.cnmide.com E-mail: sales@cnmide.com